



## GARDEX

# HOT MELT ANTI-ADHESION COMPOUND

### DESCRIPTION

GARDEX hot melt release agent is a unique formulation developed to benefit any industry that uses hot melt adhesive. The unwanted build-up of hot melt is a common problem leading to machine downtime and therefore loss of production. Temperature stable up to 220 °C  
NSF Approved: Nonfood Compounds Program Listed (H1) 148386

### AREAS OF APPLICATION

GARDEX can be used to coat the inside of all hot melt glue pots on edge banders and all melt tanks within a hot melt glue system, also use to protect daubers, drive chains, drive shafts, screw threads, temperature probes, universal joints etc.

### PACKAGING INDUSTRY

Use on all areas around glue systems including pots, nozzles, modules, hoses, chains, drainage points etc.

### WOODWORKING INDUSTRY

Apply GARDEX to all edgebanders and associated equipment.

### ECONOMICAL

Only a fine coating of GARDEX is required to treat areas. Treated glue pots stay protected for up to six months. A little goes a long way !!!

### EASY TO USE

Simply apply GARDEX with a clean cloth or sponge to all areas that become contaminated with hot (NB. Do not apply to guide rails/belts etc.)

(Easy to follow instructions are on every pack)



[www.glueguard.com](http://www.glueguard.com)



Non Citrus  
Based



Food  
Approved



Non  
Flammable



Safety  
in Use



Non Hazardous  
for Transport

GlueGuard Inc. • Guelph • Ontario • Canada  
T: 855.422.2928 • F: 855.422.2928  
Email: [info@glueguard.com](mailto:info@glueguard.com)

